

05/17/00
1c759 U.S. PTO

1c759 U.S. PTO
09/453936
05/17/00

TRANSMITTAL FORM



05/17/2000

Version: 1.0.0

Application Type: Utility Patent Filing

METHOD AND SYSTEM OF REMOTE DIAGNOSTIC, CONTROL AND INFORMATION COLLECTION USING A DYNAMIC LINKED LIBRARY OF MULTIPLE FORMATS AND MULTIPLE PROTOCOLS WITH RESTRICTION ON PROTOCOL

Application No.: 09/453,936

Attorney Docket No.: 5244-0125-2

First Named Inventor: Dr. Tetsuro MOTOYAMA

I certify that the use of this system is for OFFICIAL correspondence between patent applicants or their representatives and the USPTO. Fraudulent or other use besides the filing of official correspondence by authorized parties is strictly prohibited, and subject to a fine and/or imprisonment under applicable law.

I, the undersigned, certify that I have viewed a display of document(s) being electronically submitted to the United States Patent and Trademark Office, using either the USPTO provided style sheet or software, and that this is the document(s) I intend for initiation or further prosecution of a patent application noted in the submission. This document(s) will become part of the official electronic record at the USPTO.

Email Address: mcasey@oblon.com

Attached declaration: 125-dec.tif

Attached fee-transmittal: 52440125fee.xml

Attached specification: 125app.xml

SUBMITTED BY

Registration Number:

[illegible]

SPECIFICATION

[Electronic Version 1.0]

METHOD AND SYSTEM OF REMOTE DIAGNOSTIC, CONTROL AND INFORMATION COLLECTION USING A DYNAMIC LINKED LIBRARY OF MULTIPLE FORMATS AND MULTIPLE PROTOCOLS WITH RESTRICTION ON PROTOCOL

Abstract of the Disclosure

A method, system and computer program product for (1) collecting information from a remote application unit and/or (2) diagnosing or controlling the remote application unit. By utilizing a shareable computer code device (e.g., a dynamic linked library), a new application can utilize tested, proven code without having to reproduce existing functionality. Moreover, by supporting multiple data formats and/or multiple communication protocols, a computer code device increases the likelihood that a supported format and/or protocol will be either receivable or understandable by a receiver.

METHOD AND SYSTEM OF REMOTE DIAGNOSTIC, CONTROL AND INFORMATION COLLECTION USING A DYNAMIC LINKED LIBRARY OF MULTIPLE FORMATS AND MULTIPLE PROTOCOLS WITH RESTRICTION ON PROTOCOL

Cross-Reference to Related Applications

Referenced-applications

The present application, attorney docket number 5244-0125-2, is related to the following U.S. applications and patents: application 09/440,692 of 1999-11-16 ; application 09/440,647 of 1999-11-16 ; application 09/440,646 of 1999-11-16 ; application 09/440,693 of 1999-11-16 ; application 09/440,645 of 1999-11-16 ; application 09/408,443 of 1999-09-29 ; application 09/407,769 of 1999-09-29 ; application 09/393,677 of 1999-09-10 ; application 09/311,148 of 1999-05-13 ; application 09/192,583 of 1998-11-17 ; application 09/190,460 of 1998-11-13 ; application 08/883,492 of 1997-06-26 ; application 09/108,705 of 1998-07-01 ; application 09/107,989 of 1998-07-01 ; application 08/997,482 of 1997-12-23 ; application 08/997,705 of 1997-12-23 ; application 08/738,659 of 1996-10-30 ; application 08/738,461 of 1996-10-30 ; application 09/457,669 of 1999-12-09 ; application 08/916,009 of 1997-08-21 ; application 07/902,462 of 1992-06-19 ; application 07/549,278 of 1990-07-06 ;
5,908,493
;
5,887,216
;
5,818,603
;
5,819,110
;
5,774,678
;
5,649,120
;
5,568,618
;
5,544,289
;
5,537,554
; and
5,412,779

. This application is also related to the following co-pending applications: Attorney Docket No. 5244-0121-2; 5244-0122-2 and 5244-0126, all of which are filed on even date herewith. The contents of each of those applications and patents is incorporated herein by reference.

Statement Regarding Federally Sponsored Research

Not Applicable

Reference to a Microfiche Appendix

Not Applicable

Background of the Invention

Description of Related Art

[p1] With the rise of microprocessor-based appliances and devices, software development has clearly become a significant business. In evaluating and supporting the appliances and devices, it may be beneficial to monitor exactly how events in the appliance and device occur and how the states are changing. An example of events is an action caused by user interaction with an appliance. It may be helpful for a software developer to know which commands a user uses most often and how long those commands take to execute. Such an analysis is often referred to as "profiling." (Analogous analysis was performed on instructions in instruction sets to develop reduced instruction set computing (RISC) instructions.)

[p2] Further, in designing devices with which a human interacts, it may be desirable to monitor how the user interacts with such a device. As an example, it may be desirable to monitor how a user utilizes a control panel of an image forming device such as a photocopier, facsimile machine, printer, scanner, an appliance such as a microwave oven, VCR, digital camera, cellular phone, palm top computer, etc.

[p3] Further, it may be desirable to monitor the state of the appliances and devices to provide diagnostics, services and maintenances. Some events may be caused by the internal changes within the appliances and devices. Some events may be caused by abnormal conditions such as paper jam in the copiers. Some error conditions and warning conditions may be caused by errors in the software installed in the target appliances and devices.

[p4] Further, users are increasingly utilizing the Internet. There is significant interest in how users use the Internet, particularly with respect to how users may use certain web pages. Monitoring a user's usage of the Internet may also become significant.

[p5] It may also be desirable to determine how a user is utilizing a certain application unit (e.g., a computer running a software application, a device with an interface to be operated by a user, or a web page). The user's usage of the application unit must be monitored and effectively communicated to a remote party.

Field of the Invention

[p6] This invention generally relates to a method and system that can monitor and communicate events at plural target applications of an application unit by using at least one Dynamic Linked Library (DLL) shared among the plural target applications. DLL supports multiple data formats and multiple protocols to communicated the event data. The application unit can specify at least one protocol to be used to report the information in at least one format from the application unit. Each of the at least one protocol and each of the at least one format can be defined through the interface function.

Brief Summary of the Invention

[p7] One object of the present invention is to provide a novel and effective system for monitoring events of a target application of an application unit.

[p8] A further object of the present invention is to provide a system for communicating data obtained by monitoring events of a target application of an application unit to a remote party.

[p9] A further object of the present invention is to provide a system for communicating data obtained by monitoring events of a target application of an application unit to a remote party allowing various data formats and communication protocols to facilitate the communication system configuration and received data analysis.

[p10] A further object of the present invention is to provide a system for communicating data obtained by monitoring events of a target application of an application unit to a remote party allowing various data formats that ease the analyses of received data at the receiving side.

[p11] A further object of the present invention is to efficiently communicate the monitored event information to a transmission unit.

[p12] A further object of the present invention is to efficiently verify the combination of the two parameters specifying the format and protocol and to meet the restriction requirement on the second parameter.

[p13] The present invention achieves these and other objects by monitoring the events of a target application of an application unit. Monitoring examples include (1) monitoring a software program being executed on a computer or workstation under control of a user, (2) monitoring usage of a control panel of an image forming apparatus (e.g., a copying machine, printer, facsimile, or scanner), an appliance (e.g., a microwave oven, VCR, digital camera, cellular phone, or palm top computer), (3) monitoring any internal state changes such as error conditions and warning conditions within appliances, devices and any systems and sending the results when requested or when events occur or when preset

- [p18] Figure 4 illustrates details of the multi-port communication interface illustrated in Figure 3;
- [p19] Figure 5 illustrates an alternative system configuration in which business office devices are either connected directly to the network or connected to a computer which is connected to the network;
- [p20] Figure 6A illustrates in block diagram format the flow of information to and from an application unit using electronic mail;
- [p21] Figure 6B illustrates an alternative way of communicating using electronic mail in which the computer which is connected to the application unit also serves as a message transfer agent;
- [p22] Figure 6C illustrates an alternative way of communicating using electronic mail in which an application unit includes a message transfer agent for exchanging electronic mail;
- [p23] Figure 6D illustrates an alternative way of communicating using electronic mail in which a mail server acts as POP 3 server to receive mail for an Appliance/Device and as an SMTP server to send mail for Appliance/Device;
- [p24] Figure 7 illustrates an alternative manner of sending messages across the Internet;
- [p25] Figure 8 illustrates an exemplary computer which may be connected to the device and used to communicate electronic mail messages;
- [p26] Figure 9 is a block diagram illustrating connections between a monitoring and logging subsystem, a communications subsystem and a target application of an application unit in the present invention;

[p27] Figure 10 shows a first example of an application unit to which the present invention can be applied;

[p28] Figure 11 shows a second example of an application unit to which the present invention can be applied;

[p29] Figure 12A shows the general architecture of the system;

[p30] Figure 12B is an exemplary EventData class interface for use in the architecture of Figure 12A;

[p31] Figure 12C is an exemplary FormattedEventData class interface for use in the architecture of Figure 12A;

[p32] Figure 13 shows the calling sequence of the interface functions from application software within application unit, appliance or device;

[p33] Figure 14 shows the processing when the Application software instructs DLL to stop monitoring and send the monitored information with the specified format(s) using the specified protocol(s);

[p34] Figure 15 shows the data structure used for intelligent formatting;

[p35] Figure 16A and 16B shows the source code that implements the processing shown in Figure 14;

[p36] Figure 17 shows the data structure to handle the intelligent protocol processing with caching of the processing function;

[p37] Figures 18A through 18D show a Processor Builder class according to one embodiment of the present invention;

[p38] Figure 19 shows the processing when the Application software instructs the system to use the specified format and protocol to transmit the monitored data;

[p39] Figure 20 shows the class structure to keep track of the combination of format and protocols;

[p40] Figure 21 shows the processing of two parameters passed by the Application software through the System Manager computer code device;

[p41] Figures 22 shows the processing to get a format parameters and associated list of protocols after checking the restriction on the protocol;

[p42] Figures 23A and 23B are class specification of CFormatProtocol_InformationBase class that interface with the System Manager computer code device;

[p43] Figures 24A and 24B are class specification of CFormatProtocolCombinationCheck class to verify the combination of format and protocol; and

[p44] Figures 25A, 25B and 25C are class specification of CProtocolRestrictionCheck class where the steps in the oneFormatRestriction function shows the process to modify the map structure.

Detailed Description of the Invention

[p45] Referring now to the drawings, wherein like reference numerals designate identical or corresponding parts throughout the several views, Figure 1 illustrates (1) various machines and (2) computers for monitoring, diagnosing and controlling the operation of the machines. In Figure 1, there is a first network 16, such as a Local Area Network (LAN) connected to computer workstations 17, 18, 20 and 22. The workstations can be any type of computers including IBM Personal Computer compatible devices, Unix-based computers, or Apple Macintoshes. Also connected to the network 16 are (1) a

Delivery Status Notifications"; RFC 1939 entitled "Post Office protocol – Version 3"; and RFC 2298 entitled "An Extensible Message Format for Message Disposition Notifications." The contents of each of those references are incorporated herein by reference.

[p47] TCP/IP related communication is described, for example, in the book "TCP/IP Illustrated," Vol. 1, The Protocols, by W.R. Stevens, from Addison-Wesley Publishing Company, 1994, which is incorporated herein by reference. Volumes 1-3 of "Internetworking with TCP/IP" by Comer and Stevens are also incorporated herein by reference in their entirety.

[p48] In Figure 1, a firewall 50A is connected between the WAN 10 and the network 16. A firewall is a device that allows only authorized computers on one side of the firewall to access a network, computers or individual parts on the other side of the firewall. Firewalls are known and commercially available devices and/or software (e.g., SunScreen from Sun Microsystems Inc.). Similarly, firewalls 50B and 50C separate the WAN 10 from a network 52 and a workstation 42, respectively. Additional details on firewalls can be found in "Firewalls and Internet Security" by W. R. Cheswick, and S. M. Bellovin, 1994, Addison-Wesley Publishing, and "Building Internet Firewalls" by D. B. Chapman and E. D. Zwicky, 1995, O'Reilly & Associates, Inc. The contents of those references are incorporated herein by reference.

[p49] The network 52 is a conventional network and includes a plurality of workstations 56, 62, 68 and 74. These workstations may be in different departments (e.g., marketing, manufacturing, design engineering and customer service departments) within a single company. In addition to the workstations connected via the network 52, there is a workstation 42, which is not directly connected to the network 52. Information in a database stored in a disk 46 may be shared using proper encryption and protocols over the WAN 10 to the workstations connected directly to the network 52. Also, the workstation

42 includes a direct connection to a telephone line and/or ISDN and/or cable and/or wireless network 44 and the database in disk 46 may be accessed through the telephone line, ISDN, cable or wirelessly. The cable used by this invention may be implemented using a cable which typically is used to carry television programming, a cable which provides for high speed communication of digital data typically used with computers or the like, or any other desired type of cable.

[p50] Information of the business office machines, business devices or business office appliances 24, 28 and 32 may be stored in one or more of the databases stored in the disks 46, 54, 58, 64, 70 and 76. Known databases include (1) SQL databases by Microsoft, Oracle and Sybase (2) other relational databases, and (3) non-relational databases (including object oriented databases). Each of the customer service, marketing, manufacturing, and engineering departments may have their own database or may share one or more databases. Each of the disks used to store databases is a non-volatile memory such as a hard disk or optical disk. Alternatively, the databases may be stored in any storage device including solid state and/or semiconductor memory devices. As an example, disk 64 contains the marketing database, disk 58 contains the manufacturing database, disk 70 contains the engineering database and disk 76 contains the customer service database. Alternatively, the disks 54 and 46 store one or more of the databases.

[p51] In addition to the workstations 56, 62, 68, 74 and 42 being connected to the WAN, these workstations may also include a connection to a telephone line, ISDN, cable, or wireless network which provides a secure connection to the machine being monitored, diagnosed and/or controlled and is used during communication. Additionally, if one communication medium is not operating properly, one of the others can be automatically used for communication.

[p52] A feature of the present invention is the use of a "store-and-forward" mode of communication (e.g., Internet e-mail) or transmission between a machine and a computer for diagnosing and controlling the machine. Alternatively, the message which is transmitted may be implemented using a mode of communication that makes direct, end-to-end connections (e.g., using a socket connection to the ultimate destination).

[p53] Figure 2 illustrates the mechanical layout of the digital image forming apparatus 24 illustrated in Figure 1. In Figure 2, 101 is a fan for the scanner, 102 is a polygonal mirror used with a laser printer, and 103 designates an F lens used to collimate light from a laser (not illustrated). Reference numeral 104 designates a sensor for detecting light from the scanner. 105 is a lens for focusing light from the scanner onto the sensor 104, and 106 is a quenching lamp used to erase images on the photoconductive drum 132. There is a charging corona unit 107 and a developing roller 108. Reference numeral 109 designates a lamp used to illuminate a document to be scanned and 110, 111 and 112 designate mirrors used to reflect light onto the sensor 104. There is a drum mirror 113 used to reflect light to the photoconductive drum 132 originating from the polygon mirror 102. Reference numeral 114 designates a fan used to cool the charging area of the digital image forming apparatus, and 115 is a first paper feed roller used for feeding paper from the first paper cassette 117, and 116 is a manual feed table. Similarly, 118 is a second paper feed roller for the second cassette 119. Reference numeral 120 designates a relay roller, 121 is a registration roller. 122 is an image density sensor and 123 is a transfer/separation corona unit. Reference numeral 124 is a cleaning unit, 125 is a vacuum fan, 126 illustrates a transport belt, 127 is a pressure roller, and 128 is an exit roller. Reference numeral 129 is a hot roller used to fix toner onto the paper, 130 is an exhaust fan and 131 is the main motor used to drive the digital image forming apparatus.

[p54] Figure 3 illustrates a block diagram of the electronic components illustrated in Figure 2. The CPU 160 is a microprocessor and acts as the system controller. Random access memory (RAM) 162 stores dynamically changing information including operating parameters of the digital image forming apparatus. A non-volatile memory (e.g., a read only memory (ROM) 164 or a Flash Memory) stores (1) the program code used to run the digital image forming apparatus and (2) static-state data, describing the copier (e.g., the model number, serial number of the copier, and default parameters.

[p55] There is a multi-port network interface 166 which allows the digital image forming apparatus to communicate with external devices through at least one network. Reference number 168 represents a telephone, ISDN, or cable line, and numeral 170 represents another type of network. Additional details of the multi-port network interface are described with respect to Figure 4. An interface controller 172 is used to connect an operation panel 174 to a system bus 186. The operation panel 174 includes standard input and output devices found on a digital image forming apparatus including a copy button, keys to control the operation of the copier such as number of copies, reduction/enlargement, darkness/lightness, etc. Additionally, a liquid crystal display may be included within the operation panel 174 to display parameters and messages of the digital image forming apparatus to a user.

[p56] The local connection interface 171 is a connection through local ports such as RS232, the parallel printer port, USB, and IEEE 1394. FireWire (IEEE 1394) is described in Wickelgren, I., "The Facts About "FireWire", IEEE Spectrum, April 1997, Vol. 34, Number 4, pp. 19-25, the contents of which are incorporated herein by reference. Preferably, communication utilizes a "reliable" protocol with error detection and retransmission.

[p57] A storage interface 176 connects storage devices to the system bus 186. The storage devices include a flash memory 178 which can be substituted by a conventional EEPROM and a disk 182. The disk 182 includes a hard disk, optical disk, and/or a floppy disk drive. There is a connection 180 connected to the storage interface 176 which allows for additional memory devices to be connected to the digital image forming apparatus. The flash memory 178 is used to store semi-static state data which describes parameters of the digital image forming apparatus which infrequently change over the life of the copier. Such parameters include the options and configuration of the digital image forming apparatus. An option interface 184 allows additional hardware such as an external interface to be connected to the digital image forming apparatus. A clock/timer 187 is utilized to keep track of both the time and date and also to measure elapsed time.

[p58] On the left side of Figure 3, the various sections making up the digital image forming device are illustrated. Reference numeral 202 designates a sorter and contains sensors and actuators used to sort the output of the digital image forming device. There is a duplexer 200 which allows a duplex operation to be performed by the digital image forming device and includes conventional sensors and actuators. The digital image forming device includes a large capacity tray unit 198 which allows paper trays holding a large number of sheets to be used with the digital image forming device. The large capacity tray unit 198 includes conventional sensors and actuators.

[p59] A paper feed controller 196 is used to control the operation of feeding paper into and through the digital image forming device. A scanner 194 is used to scan images into the digital image forming device and includes conventional scanning elements such as a light, mirror, etc. Additionally, scanner sensors are used such as a home position sensor to determine that the scanner is in the home position, and a lamp thermistor is used to ensure proper operation of the scanning lamp. There is a printer/imager 192 which prints the output of the digital image forming device and includes a conventional laser printing

mechanism, a toner sensor, and an image density sensor. The fuser 190 is used to fuse the toner onto the page using a high temperature roller and includes an exit sensor, a thermistor to assure that the fuser 190 is not overheating, and an oil sensor. Additionally, there is an optional unit interface 188 used to connect to optional elements of the digital image forming device such as an automatic document feeder, a different type of sorter/collator, or other elements which can be added to the digital image forming device.

[p60] Figure 4 illustrates details of the multi-port network interface 166. The digital image forming device may communicate to external devices through a Token Ring interface 220, a cable modem unit 222 which has a high speed connection over cable, a conventional telephone interface 224 which connects to a telephone line 168A, an ISDN interface 226 which connects to an ISDN line 168B, wireless interface 228, and a LAN interface 230 (e.g., Ethernet) which connects to a LAN 170. Other interfaces (not shown) include, but are not limited to, Digital Subscriber Line (DSL) (original DSL, concentric DSL, and asymmetric DSL). A single device which connects to both a Local Area Network and a telephone line is commercially available from Megahertz and is known as the Ethernet-Modem.

[p61] The CPU or other microprocessor or circuitry executes a monitoring process to monitor the state of each of the sensors of the digital image forming device, and a sequencing process is used to execute the instructions of the code used to control and operate the digital image forming device. Additionally, there is (1) a central system control process executed to control the overall operation of the digital image forming device and (2) a communication process used to assure reliable communication to external devices connected to the digital image forming device. The system control process monitors and controls data storage in a static state memory (e.g., the ROM 164 of Figure 3), a semi-static memory (e.g., the flash memory 178 or disk 182), or the dynamic state memory (e.g., a volatile or non-volatile memory (e.g., the RAM 162 or the flash

memory 178 or disk 182)). Additionally, the static state memory may be a device other than the ROM 164 such as a non-volatile memory including either of the flash memory 178 or disk 182.

[p62] The above details have been described with respect to a digital image forming device but the present invention is equally applicable to other business office machines or devices such as an analog copier, a facsimile machine, a scanner, a printer, a facsimile server, or other business office machines and business office appliance, or appliances (e.g., a microwave oven, VCR, digital camera, cellular phone, palm top computer). Additionally, the present invention includes other types of devices which operate using store-and-forward or direct connection-based communication. Such devices include metering systems (including gas, water, or electricity metering systems), vending machines, or any other mechanical device (e.g., automobiles) that need to be monitored during operation or remote diagnosis. In addition to monitoring special purpose machines and computers, the invention can be used to monitor, control, and diagnose a general purpose computer which would be the monitored and/or controlled device.

[p63] Figure 5 illustrates an alternative system diagram of the invention in which different devices and subsystems are connected to the WAN 10. However, there is no requirement to have each of these devices or subsystems as part of the invention. Each component or subsystem illustrated in Figure 5 is individually part of the invention. Further, the elements illustrated in Figure 1 may be connected to the WAN 10 which is illustrated in Figure 5. In Figure 5, there is illustrated a firewall 50-1 connected to an intranet 260-1. The service machine 254 connected to the intranet 260-1 includes therein or has connected thereto data 256 which may be stored in a database format. The data 256 includes history, performance, malfunction, and any other information including statistical information of the operation or failure or set-up and components or optional equipment of devices which are being monitored. The service machine 254 may be

implemented as the device or computer which requests the monitored devices to transmit data or which requests that remote control and/or diagnostic tests be performed on the monitored devices. The service machine 254 may be implemented as any type of device and is preferably implemented using a computerized device such as a general purpose computer.

[p64] Another sub-system of Figure 5 includes a firewall 50-2, an intranet 260-2, and a printer 262 connected thereto. In this sub-system, the functions of sending and receiving electronic messages by the printer 262 (and similarly by a copier 286) are performed by (1) circuitry, (2) a microprocessor, or (3) any other type of hardware contained within or mounted to the printer 262 (i.e., without using a separate general purpose computer).

[p65] An alternate type of sub-system includes the use of an Internet service provider 264 which may be any type of Internet service provider (ISP), including known commercial companies such as America Online, Earthlink, and Niftyserve. In this sub-system, a computer 266 is connected to the ISP 264 through a digital or analog modem (e.g., a telephone line modem, a cable modem, modems which use any type of wires such as modems used over an ISDN (Integrated Services Digital Network) line, ASDL (Asymmetric Digital Subscriber Line), modems which use frame relay communication, wireless modems such as a radio frequency modem, a fiber optic modem, or a device which uses infrared light waves). Further, a business office device 268 is connected to the computer 266. As an alternative to the business office device 268 (and any other device illustrated in Figure 5), a different type of machine may be monitored or controlled such as a digital copier, any type of appliance, security system, or utility meter such as an electrical, water, or gas utility meter, or any other device discussed herein.

[p66] Also illustrated in Figure 5 is a firewall 50-3 connected to a network 274. The network 274 may be implemented as any type of computer network, (e.g., an Ethernet or token-ring network). Networking software which may be used to control the network includes any desired networking software including software commercially available from Novell or Microsoft. The network 274 may be implemented as an Intranet, if desired. A computer 272 connected to the network 274 may be used to obtain information from a business office device 278 and generate reports such as reports showing problems which occurred in various machines connected to the network and a monthly usage report of the devices connected to the network 274. In this embodiment, a computer 276 is connected between the business office device 278 and the network 274. This computer receives communications from the network and forwards the appropriate commands or data, or any other information, to the business office device 278. Communication between the business office device 278 and the computer 276 may be accomplished using wire-based or wireless methods including, but not limited to radio frequency connections, electrical connections and light connections (e.g., an infrared connection, or a fiber optics connection). Similarly, each of the various networks and intranets illustrated in Figure 5 may be established using any desired manner including through the establishment of wireless networks such as radio frequency networks. The wireless communication described herein may be established using spread spectrum techniques including techniques which use a spreading code and frequency hopping techniques such as the frequency hopping wireless technique which is disclosed in the Bluetooth Specification (available at the world wide web site www.bluetooth.com), which is incorporated herein by reference.

[p67] Another sub-system illustrated in Figure 5 includes a firewall 50-4, an intranet 260-4, a computer 282 connected thereto, a business office appliance 285 and a copier 286. The computer 282 may be used to generate reports and request diagnostic or control procedures. These diagnostic and control procedures may be performed with respect to the business office appliance 285 and the copier 286 or any of the other devices illustrated in or used with Figure 5. While Figure 5 illustrates a plurality of firewalls, the firewalls are preferable but optional equipment and therefore the invention may be operated without the use of firewalls, if desired.

application unit's usage.

[p69] From the message transfer agents 312, e-mail messages are stored in user mailboxes 314 which are transferred to the mail agent 316 and ultimately transmitted to the user at a terminal 318 which functions as a receiving terminal.

[p70] This "store-and-forward" process avoids the sending mail agent 304 from having to wait until establishment of the direct connection with the mail recipient. Because of network delays, the communication could take a substantial amount of time during which the application would be unresponsive. Such an unresponsiveness is generally unacceptable to users of the application unit. By using e-mail as the store-and-forward process, retransmission attempts after failures occur automatically for a fixed period of time (e.g., three days). In an alternate embodiment, the application can avoid waiting by passing communicating requests to one or more separate threads. Those threads can then control communication with the receiving terminal 318 while the application begins responding to the user interface again. In yet another embodiment in which a user wishes to have communication completed before continuing, direct communication with the receiving terminal is used. Such direct communication can utilize any protocol not blocked by a firewall between the sending and receiving terminals. Examples of such protocols include FTP and HTTP.

[p71] Public WANs, such as the Internet, are not considered to be secure. Therefore, messages transmitted over the public WANs (and multi-company private WANs) should be encrypted to keep the messages confidential. Encryption mechanisms are known and commercially available which may be used with the present invention. For example, a C library function, crypto, is available from Sun Microsystems for use with the Unix operating system. Other encryption and decryption software packages are known and commercially available and may also be used with this invention. One such package is PGP Virtual Private Network (VPN) available from Network Associates. Other VPN

software is available from Microsoft Corporation.

[p72] As an alternative to the general structure of Figure 6A, a single computer may be used which functions as the computer interface 302, the mail agent 304, the mail queue 306 and the message transfer agent 308. As illustrated in Figure 6B, the Device/Appliance 300 is connected to a computer 301 which includes the message transfer agent 308.

[p73] A further alternative structure is shown in Figure 6C in which the message transfer agent 308 is formed as part of the Device/Appliance 300. Further, the message transfer agent 308 is connected to the message transfer agent 312 by a TCP/IP connection 310. In the embodiment of Figure 6C, the Device/Appliance 300 is directly connected to the TCP/IP connection 310 and has an e-mail capability. One use of the embodiment of Figure 6C includes using a facsimile machine with an e-mail capability (defined in RFC 2305 (a simple mode of facsimile using Internet mail)) as the Device/Appliance 300.

[p74] Figure 6D shows a system where an appliance or a device does not itself have the capability to receive directly e-mail, but uses the POP3 protocol to retrieve the received mail from mail server.

[p75] Figure 7 illustrates an alternative implementation of transferring mail and is based on Figure 28.3 of Stevens. Figure 7 illustrates an electronic mail system having a relay system at each end. The arrangement of Figure 7 allows one system at an organization to act as a mail hub. In Figure 7, there are four MTAs connected between the two mail agents 304 and 316. These MTAs include local MTA 322A, relay MTA 328A, relay MTA 328B, and local MTA 322D. The most common protocol used for mail messages is SMTP (Simple Mail Transfer Protocol) which may be used with this invention, although any desired mail protocol may be utilized. In Figure 7, 320 designates a sending host which includes the computer interface 302, the mail agent 304, and the local MTA 322A.

The Device/Appliance 300 is connected to, or alternatively included within, the sending host 320. As another case, the Device/Appliance 300 and host 320 can be in one machine where the host capability is built into the Device/Appliance 300. Other local MTAs 322B, 322C, 322E and 322F may also be included. Mail to be transmitted and received may be queued in a queue of mail 306B of the relay MTA 328A. The messages are transferred across the TCP/IP connection 310 (e.g., an Internet connection or a connection across any other type of network).

[p76] The transmitted messages are received by the relay MTA 328B and if desired, stored in a queue of mail 306C. The mail is then forwarded to the local MTA 322D of a receiving host 342. The mail may be placed in one or more of the user mailboxes 314 and subsequently forwarded to the mail agent 316 and finally forwarded to the user at a terminal 318. If desired, the mail may be directly forwarded to the terminal without user interaction.

[p77] The various computers utilized by the present invention, including the computers 266 and 276 of Figure 5, may be implemented as illustrated in Figure 8. Further, any other computer utilized by this invention may be implemented in a similar manner to the computer illustrated in Figure 8, if desired, including the service machine 254, computer 272, and computer 282 of Figure 5. However, not every element illustrated in Figure 8 is required in each of those computers. In Figure 8, the computer 360 includes a CPU 362 which may be implemented as any type of processor including commercially available microprocessors from companies such as Intel, AMD, Motorola, Hitachi and NEC. There is a working memory such as a RAM 364, and a wireless interface 366 which communicates with a wireless device 368. The communication between the interface 366 and device 368 may use any wireless medium (e.g., radio waves or light waves). The radio waves may be implemented using a spread spectrum technique such as Code Division Multiple Access (CDA) communication or using a frequency hopping technique

such as that disclosed in the Bluetooth specification.

[p78] There is a ROM 370 and a flash memory 371, although any other type of non-volatile memory (e.g., EPROM, or an EEPROM) may be utilized in addition to or in place of the flash memory 371. An input controller 372 has connected thereto a keyboard 374 and a mouse 376. There is a serial interface 378 connected to a serial device 380. Additionally, a parallel interface 382 is connected to a parallel device 384, a universal serial bus interface 386 is connected to a universal serial bus device 388, and also there is an IEEE 1394 device 400, commonly referred to as a fire wire device, connected to an IEEE 1394 interface 398. The various elements of the computer 360 are connected by a system bus 390. A disk controller 396 is connected to a floppy disk drive 394 and a hard disk drive 392. A communication controller 400 allows the computer 360 to communicate with other computers (e.g., by sending e-mail messages) over a telephone line 402 or a network 404. An I/O (Input/Output) controller 408 is connected to a printer 410 and a hard disk 412, for example using a SCSI (Small Computer System Interface) bus. There is also a display controller 416 connected to a CRT (Cathode Ray Tube) 414, although any other type of display may be used including a liquid crystal display, a light emitting diode display, a plasma display, etc.

[p79] One feature in the present invention is to monitor how a user uses a target application of an application unit. The term application unit in this instance refers to a system which a user interacts with and controls. A "target application" refers to a user controlled system that controls the application unit. For example, an application unit may typically be a computer and a target application may then be a software program, e.g. a word processor, running on the computer which a user operates, for example by moving a pointer on a computer screen and "clicking" on certain command icons to cause the software program to perform certain functions. In this sense, an application unit in the present invention can refer to any of workstations 17, 18, 20, 22, 56, 62, 68, 74, 42 shown

in Figure 1 running a software program, the computer 301 shown in Figure 6B running a software program, etc. An application unit can also refer to an image forming device such as any of the digital image forming apparatus 24, facsimile machine 28, and printer 32 in Figures 1 and 2. In this instance, each of these device application units includes a user interface, such as operation panel 174 (see Fig. 3), which a user interacts with and utilizes to control the device application unit. The present invention can monitor a user selecting controls on such an operation panel. As a further example, the application unit could also be an appliance, such as a microwave oven, with an operation panel. An application unit can also refer to any other device, including software, with which a user interacts, and in this case the target application may refer to only one feature of the software which the user interacts with.

[p80] One feature of the present invention is to monitor the user's usage of such a target application of an application unit, and to communicate data of the monitored usage. This data will typically be transmitted by e-mail by the computer interface 302 of Figure 6A, or the computer 301 of Figure 6B or the Device/Appliance 300 of Figure 6C. This data of a user's usage of a target application of an application unit can then be utilized in many ways, for example in improving software development, in monitoring usage of a device (e.g., an image forming device), discovering user difficulties with appliances and software, and finding most frequently used features of application units.

[p81] Figure 9 shows various elements of the present invention. More particularly, Figure 9 shows an Device/Appliance 300 including target applications 510, 512 and 513. The user interface 510 is an interface for a user to control the appliance or device. As discussed above, in one common instance, the target appliance 300 may be a software program running on one of the workstations 17, 18, 20, 22 (Figure 1) of the present specification. In this instance, the user interface 510 may be a display on a monitor of one of these workstations. In such a case, the monitoring system 515 may monitor the user

behavior of clicking the selected menu. Another application may be that the appliance 300 is a copier where "application 2" (512) is a sorting of the multiple copies. Both User interface 510 and "Application 2" (512) would send event messages to Monitoring System 515 to be logged. The Monitoring System 515 is implemented either only in hardware or using a combination of hardware and software where the combination includes at least one computer readable medium. Examples of computer readable media are compact discs 119, hard disks 112, floppy disks, tape, magneto-optical disks, PROMs (EPROM, EEPROM, Flash EPROM), DRAM, SRAM, SDRAM, etc. Stored on any one or on a combination of computer readable media, the present invention includes software for controlling both the hardware and for enabling the system to interact with a human user. Such software (in the form of computer code devices) may include, but is not limited to, device drivers, operating systems and user applications, such as development tools. Such computer readable media further includes the computer program product of the present invention for monitoring and controlling an application unit. The computer code devices of the present invention can be any interpreted or executable code mechanism, including but not limited to scripts, interpreters, dynamic link libraries, classes (e.g., Java or C++), packages (e.g., Java or C++) and complete executable programs.

[p82] Another illustrative embodiment of Figure 9 is an office device such as a digital copier where Application 1 (510) is the aforementioned user interface. Application 2 (512) is the software error tracking system to monitor the internal error conditions of the software system. Application 3 (513) is the mechanical error tracking system to monitor the mechanical error condition such as jam and toner out. All of the applications are using the Monitoring System (515) and Sending Block (520). As a further example, and as noted above, the Device/Appliance 300 may be an image forming device such as the digital image forming apparatus 26, facsimile machine 28, or printer 32 also shown in Figure 1. In this instance, the user interface 510 may take the form of an operation panel

(e.g., operation panel 174 in Fig. 3) with a plurality of keys and/or a touch screen which a user operates to control the image forming device. When the Device/Appliance 300 in Figure 9 is an image forming device with a user interface 510, the present invention can monitor the commands that a user selects.

[p83] At a designated time, the logged data of the events is then sent to the sending block 520, which then communicates such monitored event data to a designated party. The monitoring and logging DLL 515 can be implemented in the device including the Device/Appliance 300 or in another system control element. The protocol processing system can also be implemented in the device including the application unit in Figure 6C, or can also be implemented in the computer 301 in Fig. 6B to which the application unit is attached. The present invention can also take the form of computer control codes recorded on a computer readable medium.

[p84] One illustrative embodiment of such a user interface 510 used with a digital image forming apparatus 26, facsimile machine 28, or printer 32 is shown in Figure 11. In that embodiment, the present invention monitors each time a user presses one of the control buttons on the operation panel and logs the usage data of such a user usage for subsequent communication.

[p85] As shown in Figure 11, such an operation panel 700 may include a touch screen 705 on which various commands may appear which an operator can select by touching different portions of the touch screen 705. The operation panel 700 may also include a 10-key pad 710 and various other control buttons 715. In the case of an image forming device, the control buttons 715 may be commands for selecting a paper size, changing a magnification, changing a darkness of a desired image, etc.

[p86] When the Device/Appliance 300 in Figure 9 is an image forming device and the user interface 510 corresponds to the operation panel 700 as shown in Figure 11, the present invention can monitor the commands (shown in Figure 11) that a user selects. The operation panel 700 shown in Figure 11 may, with modifications, also be an operation panel for a user-controlled appliance such as a microwave oven, VCR, digital camera, cellular phone, palm top computer, etc.

[p87] Figures 10 and 11 show examples of the Device/Appliance 300 and user interface 510 of Figure 9 to which the present invention can be applied. As would be readily apparent to those of ordinary skill in the art, the present invention is directed to various types of application units including various types of user interfaces. The present invention is applicable to any device to be monitored which includes a user interface.

[p88] Figure 12 shows the general event management architecture of the system that can be implemented as any one, or a combination of, a dynamic linked library (DLL), a script, a Java or C++ class, a C library or routine, etc. The remainder of this discussion describes the implementation in terms of a DLL. In general, an application 510 communicates through an interface 550. The interface 550 specifies the API for the event management architecture (e.g., how information is passed via a C function call to the object(s) in the System Manager 560 with the same names). The System Manager computer code device 560 manages the behavior of other computer code devices by using appropriate objects and their functions. Similarly, the Event Logger 565 records all the necessary information such as User ID, Application ID, Cumulative Session Number, Start Time, Duration and Sequence of Events with the elapsed times when requested through the system manager 560. The Event Logger supports functions including: initialize(), storeEvent (), stopMonitoring(), and getEventData().

[p89] The initialize function receives a string parameter for the Application ID. The System Manager 560 calls this function when startMonitoring is called by an application 510. The function sets the Application ID, takes care of the Cumulative number of usages, reads the clock to store the start time in order to compute the elapse time and duration, and sets up the user information by examining the registry.

[p90] The initialize function receives a string parameter for the Application ID. The System Manager 560 calls this function when startMonitoring is called by an application 510. The function sets the Application ID, takes care of the Cumulative number of usages, reads the clock to store the start time in order to compute the elapse time and duration, and sets up the user information by examining the registry.

[p91] After the application 510 has completed its usage monitoring, it calls the stopMonitoring function so that the duration can be computed. If multiple sessions are stored, this function stops the recording of a corresponding session.

[p92] After initialization, the `storeEvent()` function can be called with a string parameter for the Event passed by `recordEvent`. The `EventLogger` 565 stores the event string and the elapsed time from the start time (recorded during the `initialize()` function call).

[p93] The EventLogger 565 also provides access to a `getEventData` function. If the `stopMonitoring` was not previously called (i.e., the current session's duration field is undefined), the monitoring is stopped by calling the `stopMonitoring` function. The `stopMonitoring` function computes the duration of the current session. The `getEventData` function returns an abstract class with the access functions shown in Figure 12B. The abstract class facilitates extensions for multiple sessions.

[p94] The Format And Protocol Information Base System 570 (implemented as any one or a combination of package, DLL, static library, etc.) stores the format and protocol information and checks the combination of formats and protocols to determine the valid combinations. To facilitate the storage process, the storeFormatAndProtocol function accepts two parameters (i.e., one for format and one for protocol). The function checks to ensure that the parameters are a valid combination.

[p95] The component 570 also includes a getFormatAndProtocolVector function returns a format and associated vector of protocols. In one embodiment, the function performs error checking. For example, if a protocol allows only one format to be sent, then the format should be the last format in the function call of selectFormatProtocol. The return value is a boolean value where true indicates that valid parameters were returned and false indicates that no more data is available. The return parameters are int and vector of int. The first int refers to the format while the vector of int refers to the vector of protocols for the format. When there is no selectFormatProtocol function call, the getFormatAndProtocolVector returns the default setting. Also would be evident, other collections (e.g., a list template) may be used in place of a vector.

[p96] The Data Format Processor 575 is responsible for formatting event data into a specified format. One exemplary function is the formatEventData function that receives a pointer to the abstract class EventData. The return value is a pointer to the abstract class FormattedEventData. Generally, interface to the FormattedEventData abstract class is defined as in Figure 12C.

[p97] The Protocol Processor 580 is responsible for outputting the formatted event data through the specified protocol. In one embodiment, the processor 580 also encrypts the body of message. To output the data, the processFormattedData function is called with an input pointer to the abstract class FormattedEventData. The function returns a boolean

value where "true" represents no errors, and "false" represents the existence of an error while processing the formatted data.

[p98] The System 585 supplies important information and persistent information across the execution of the DLL. Some of the important information is timer information through the library call. The registry to keep the necessary information is another important component of the System 585. Many registry entries are set up at installation time. An exemplary structure for the registry is:

[p99] HKEY_LOCAL_MACHINE -- SOFTWARE -- RicohMonitor -- XXX
(ApplicationID)

[p100] Where XXX represents the Application ID, the following variables are placed in the registry under XXX tree: CumulativeUsage, UserID, SMTP Server, Recipients, From, FTP Server, FTP User, FTP Password, FTP Target Path etc. In one embodiment, CumulativeUsage is an integer, and the rest of the variables are strings.

[p101] Figure 13 shows an exemplary calling sequence of various computer code devices according to the present invention. The application software sets up the Application ID and starts the monitoring computer code device. When the events to be monitored happen, the application sends a message to the monitoring computer code device with the event name so that monitoring computer code device will keep track of the name of event and the timing. When the application no longer needs to monitor any activities, the application sends a command to select the format and protocol to be used to send the monitored information. The application then calls the stopMonitoring function, either explicitly or implicitly, as described below. Although Figure 13 describes sending the monitored information each time an application stops monitoring, in an alternate embodiment, information is sent only upon a secondary event happening (e.g., elapsed time or after a number of events or monitoring sessions have occurred).

[p102] Figure 14 describes the process of sending the monitored information (e.g., when the monitoring stops as shown in Figure 13). After the stopMonitoring request has propagated from the Target Application (through the CMonitorSeqApp (in step 1)) to the CMonitorManager (in step 2) which passes the request to the EventLogger system (in step 3). The CMonitorManager coordinates subsequent communication between the other computer code devices. The first such communication is in response to a getEventData request made by the CMonitorManager. In step 5, CMonitorManager obtains a format and associated vector of protocols from CformatAndProtocolInformationBase. Later, step 6, entitled "CreateDataFormatProcessor," creates the data formatter for the selected formatting that is used to format the monitored event data in step 7. Step 8 obtains the protocol processor specified by the application software before stopping monitoring. Together, steps 6 and 8 show that the formatters and protocol processors can be created dynamically (i.e., only when they are needed). In addition, created protocol processors can be cached in the CProcessorBuilder.

[p103] Figure 15 shows the map data structure used for creating the DataFormat Processor. A map includes at least one (key, value) pair. By using a key (corresponding to one of the possible data formats) as an index value into the map, the system selects a corresponding pointer to a function that creates the data formatter that will transform the monitored event data into the specified data format. When the specified format is sent to the ProcessorBuilder in Figure 14, the corresponding value in the map for the format is the function pointer to create the formatter. The function pointed by the pointer is to create the requested data formatter. Therefore, the formatter itself is not actually created until the function pointed to by the pointer is executed. In addition, the class returned by this function is the abstract class entitled "data formatter." Accordingly, the user of the class does not need to know the details of the returned formatter, just the abstract class

that defines its basic functions.

[p104] Figures 16A and 16B are exemplary code embodiments corresponding to the Figure 14. Step 4 in the source code correspond to getting the specified formatter (step 6 of the Figure 14) while step 5 of the source code formats the data (step 7 of the Figure 14).

[p105] While the above discussion has generally focused on using a single protocol and/or a single data format, in an alternate embodiment, the present invention utilizes plural protocols and/or plural data formats. Those protocols and formats can include, but are not limited to any of the protocols and formats discussed herein. Exemplary formats include, but are not limited to, uncompressed or compressed versions of any one of: un-delimited text, SGML, XML, HTML, csv format, and binary. This enhances the number of possible ways that data can be transferred to support the monitoring of the present invention. Accordingly, one implementation of the application sends at least one (format, protocol) pair to be used by the computer code device (e.g., DLL). The computer code device checks that each pair is valid before storing it in the data structure of two maps. For example, if the format specifies the binary encoding of fixed format, but the protocol is SMTP with the plain text encoding in the mail body, the format and protocol are not a valid pair/combination. Before the monitored data are sent out, the computer code device checks if a selected protocol is restricted to support only one format. Two maps are used for this purpose. Then, the system utilizes the specified data format one at a time to generate the required format and sends out the generated data over all the protocol specified for this data format.

[p106] The present invention is also applicable to implementations where two different kinds of parameters are specified multiple times where the first parameter processing is more costly than the second parameter processing. In addition, the some second parameter values may be restricted to supporting only one first parameter value that is

specified last. In such a case, the present invention technique can be utilized to process the system efficiently.

[p107] Figure 17 shows the map data structure (using (key, value) pairs) used for creating and caching the protocol processor. In one embodiment, for a given formatted event data, multiple protocols may need to send the same event data. Likewise, the same protocol may be requested to send the same data using different data formats. As discussed above, the key of each pair specifies a protocol (e.g., SMTP, FTP or HTTP) to be used. The value of the map is itself a second pair (x,y), where x is a pointer to the protocol processor object, and where y is a pointer to the function that creates the protocol processor. This map is initialized to contain the keys and values with the x value being assigned a flag value (e.g., zero). When a particular protocol is requested, the x value corresponding to the specified key is checked. If the x value is zero, the function pointed to by y value is executed. That execution creates the protocol processor, and the pointer to the created object is stored in the x value. Then, the newly created or subsequently stored pointer to the object is then returned as a pointer to the abstract class. Step 6 of Figures 16A and 16B (corresponding to step 8 of Figure 14) illustrates an exemplary code fragment that calls the createProtocolProcessor function. The createProtocolProcessor function returns a pointer to the abstract protocol processor object (identified by the return type "CAbsProtocolProcessor *"). Step 7 of Figure 16B (corresponding to the step 9 of Figure 14) shows sending monitored information in a requested format.

[p108] Figure 18A shows the function list and the attributes of the CProcessorBuilder Class according to one embodiment of the present invention. The public function createDataFormatProcessor receives the specification for the Data Formatter and returns the pointer to the specified Data Formatter object in the abstract class type. The public function createProtocolProcessor function receives the specification for the Protocol

Processor and returns the pointer to the specified Protocol Processor in the abstract class type. The m_pDataFormatter attribute of the class is used to cache the specified data formatter in the class. The other two map attributes show the structure shown in the Figures 15 and 17. The function definition section shows the steps used by the various functions declared in the function list.

[p109] Figure 19 illustrates three exemplary steps that pass the format and protocol parameters from the Target Application to the Format and Protocol Information Base System to enable plural protocols and/or formats to be used. Similar to transferring a stopMonitoring request in Figure 14, Figure 19 shows how a selectFormatProtocol request is passed from the Target Application through the CMonitorSeqApp to the CMonitorManager. The CMonitorManager converts the request into a storeFormatAndProtocol request that is passed on to the Format and Protocol Information Base System, thereby storing the format and protocol information. Although the parameters are illustrated as integers, any type can be used that uniquely specifies the format and protocol. As would be evident, the functions can return either nothing or an error code.

[p110] Figure 20 shows relationships of the CFormatProtocolCombinationCheck class 610 and the CProtocolRestrictionCheck class 620 used within the Format And Protocol Information Base System. Generally, the CFormatProtocol_InformationBase interface 600 (described in more detail with reference to Figures 23A and 23B) keeps track of the specified formats and protocols. That interface 600 uses the (1) CFormatProtocolCombinationCheck class 610 and (2) the CProtocolRestrictionCheck class 620 for (1) verifying requested combinations and (2) checking for restrictions on the protocols, respectively.

[p111] Figure 21 describes the process by which the system manager 560 verifies whether a specified format and protocol combination is valid. A storeFormatAndProtocol request from the system manager 560 is initially handled by the CFormatProtocol_InformationBase interface 600. Using the relationships illustrated in Figure 20, that interface 600 converts the request to an isFormatProtocolCombinationOK request that is sent on to the CFormatProtocolCombinationCheck class 610. If that class 610 returns "true," then the combination is valid; otherwise, the class 610 returns false indicating that the combination is invalid. When the combination is valid, the two values are stored into two different maps specified in the Figure 23A.

[p112] Figure 22 describes the process of returning the format and list of protocols. In Figure 22, int and vector are exemplary output parameters, but other implementations may use other containers (e.g., the list template of the standard template library) to facilitate the restriction check. Generally, the system manager 560 sends a getFormatAndProtocolVector request to the CFormatProtocol_InformationBase interface 600. Using the relationships illustrated in Figure 20, that interface 600 converts the request to a getFormatProtocolVectorMapAfterCheckingProtocolRestriction request that is sent on to the CProtocolRestrictionCheck class 620.

[p113] Figure 23A is an exemplary class definition of CFormatProtocol_InformationBase interface/class. The functions, storeFormatAndProtocol and getFormatAndProtocolVector, are public functions used by the System Manager 560 computer code device (an object of CMonitorManager class). Two map structures keep the specified formats and protocols passed through the function, storeFormatAndProtocol, after checking the validity of the combination of the format and the protocol through the object, m_FormatProtocolCombinationCheck of CFormatProtocolCombinationCheck class. The class also contains the object,

m_ProtocolRestrictionCheck of CProtocolRestrictionCheck class. The flag, m_bFirstGetCall is used to call the function in the m_ProtocolRestrictionCheck when the function getFormatAndProtocolVector is called for the first time. The attribute, m_FormatProtocolVectorMapIterator, is used by the getFormatAndProtocolVector function to iterate over the m_FormatProtocolVectorMap. Figure 23B shows the steps for three main functions in the CFormatProtocol_InformationBase class 600.

[p114] Figures 24A and 24B show the class definition of CFormatProtocolCombinationCheck class 610. The main responsibility of the class 610 is to check whether a specified format and protocol combination is valid. The map, m_CombinationMartix, contains the information of the valid combination that is initialized by the function initMatrix.

[p115] Figures 25A, 25B, and 25C show the class definition of the CProtocolRestrictionCheck class 620. The m_bOneFormatRestriction attribute specifies whether the information is restricted to a single format. Other types of restrictions could be implemented by adding other private functions and attributes. An exemplary restriction algorithm for the present invention is illustrated in Figures 25B and 25C (showing the steps in the private function oneFormatRestriction).

[p116] Obviously, numerous modifications and variations of the present invention are possible in light of the above teachings. It is therefore to be understood that, within the scope of the appended claims, the invention may be practiced otherwise than as specifically described herein.

Deposit of Computer Program Listings

Not Applicable

2025 RELEASE UNDER E.O. 14176

What is Claimed is:

- [c1] A computer program product, comprising: a computer storage medium and a computer program code mechanism embedded in the computer storage medium for controlling a combination of a protocol and a format used to communicate event data between a remote receiver and at least one of a device, an appliance, an application and an application unit, the computer program code mechanism comprising: a first computer code device configured to select a protocol to transfer event data between the remote receiver and the at least one of a device, an appliance, an application and an application unit; a second computer code device configured to select a first format to transfer event data between the remote receiver and the at least one of a device, an appliance, an application and an application unit; and a third computer code device configured to determine if the protocol selected by the first computer code device is compatible with the first format selected by the second computer code device.
- [c2] The computer program product as claimed in claim 1, further comprising a fourth computer code device configured to select a second format to transfer event data between the remote receiver and the at least one of a device, an appliance, an application and an application unit if the first format is not compatible with the protocol selected, wherein the third computer code device is further configured to determine if the protocol selected by the first computer code device is compatible with the second format selected by the fourth computer code device.
- [c3] The computer program product as claimed in claim 1, further comprising: a fourth computer code device configured to select a second format to transfer event data between the remote receiver and the at least one of a device, an appliance, an application and an application unit after selecting the first format; and a fifth computer code device configured to transmit data to the remote receiver from the at least one of a device, an appliance, an

application and an application unit only using the second format if the protocol supports only one format at a time.

[c4] The computer program product as claimed in claim 1, further comprising: a fourth computer code device configured to select a second format to transfer event data between the remote receiver and the at least one of a device, an appliance, an application and an application unit after selecting the first format; and a fifth computer code device configured to transmit data to the remote receiver from the at least one of a device, an appliance, an application and an application unit sequentially using the first and second formats if the protocol supports plural formats at a time.

[c5] The computer program product as claimed in claim 1, further comprising: a fourth computer code device configured to select a second format to transfer event data between the remote receiver and the at least one of a device, an appliance, an application and an application unit after selecting the first format; and a fifth computer code device configured to transmit data to the remote receiver from the at least one of a device, an appliance, an application and an application unit in parallel using the first and second formats if the protocol supports plural formats at a time.

[c6] The computer program product as claimed in claim 1, wherein: the first computer code device comprises a fourth computer code device configured to store a first indicator, corresponding to the protocol selected, in a map entry of a map; and the second computer code device comprises a fifth computer code device configured to store a second indicator, corresponding to the first format, in the map entry.

[c7] The computer program product as claimed in claim 6, wherein the third computer code device comprises a sixth computer code device configured to compare the first and second indicators stored in the map against values in a data structure corresponding to at least one compatible format for a specified protocol.

- [c8] The computer program product as claimed in claim 6, wherein the third computer code device comprises a sixth computer code device configured to compare the first and second indicators stored in the map against values in a data structure corresponding to at least one compatible protocol for a specified format.
- [c9] The computer program product as claimed in claim 6, wherein the third computer code device comprises a sixth computer code device configured to iterate over values in a data structure corresponding to at least one compatible protocol for a specified format.
- [c10] The computer program product as claimed in claim 6, wherein the third computer code device comprises a sixth computer code device configured to iterate over values in a data structure corresponding to at least one compatible format for a specified protocol.
- [c11] The computer program product as claimed in claim 1, wherein at least one of the first through third computer code devices comprise a library of code shared between first and second applications.
- [c12] The computer program product as claimed in claim 1, wherein at least one of the first through third computer code devices comprise a dynamically linked library of code shared between first and second applications.
- [c13] A computer-implemented method for controlling a combination of a protocol and a format used to communicate event data between a remote receiver and at least one of a device, an appliance, an application and an application unit, comprising: selecting a protocol to transfer event data between the remote receiver and the at least one of a device, an appliance, an application and an application unit; selecting a first format to transfer event data between the remote receiver and the at least one of a device, an appliance, an application and an application unit; and determining if the protocol selected is compatible with the first format selected.

[c14] The method as claimed in claim 13, further comprising: selecting a second format to transfer event data between the remote receiver and the at least one of a device, an appliance, an application and an application unit if the first format is not compatible with the protocol selected; and determining if the protocol selected is compatible with the second format selected.

[c15] The method as claimed in claim 13, further comprising: selecting a second format to transfer event data between the remote receiver and the at least one of a device, an appliance, an application and an application unit after selecting the first format; and transmitting data to the remote receiver from the at least one of a device, an appliance, an application and an application unit only using the second format if the protocol supports only one format at a time.

[c16] The method as claimed in claim 13, further comprising: selecting a second format to transfer event data between the remote receiver and the at least one of a device, an appliance, an application and an application unit after selecting the first format; and transmitting data to the remote receiver from the at least one of a device, an appliance, an application and an application unit sequentially using the first and second formats if the protocol supports plural formats at a time.

[c17] The method as claimed in claim 13, further comprising: selecting a second format to transfer event data between the remote receiver and the at least one of a device, an appliance, an application and an application unit after selecting the first format; and transmitting data to the remote receiver from the at least one of a device, an appliance, an application and an application unit in parallel using the first and second formats if the protocol supports plural formats at a time.

Page 44 of 79





FIG. 2






FIG. 4




FIG. 5




FIG. 6A




FIG. 6B




FIG. 6C




Figure 6D





FIG. 7






Fig. 9

Figure 10





Figure 11






Figure 12A

Return Value	Function Name	Description
bool	getNextSession	Returns false when there is no more session; true otherwise
string	getFileName	Returns file name for the EventData
map<string, string>	getSessionInformation	Returns the map. Keys are UserID, ApplicationID, CumulativeSessionNumber, StartTime, and Duration.
map<string, vector<string>>	getSessionEventData	Returns the map. Keys are EventName and EventTiming. The values of EventTiming vector are in the unit of 10th of a second converted from unsigned integer to string.

Figure 12B

Return Value	Function Name	Description
bool	getNextLine	Returns one line of string data as an out parameter string. The function returns true if there is a line; false if no more line exists with empty string.
string	getFileNameWithSuffix	Returns file name for the data with suffix if applicable

Figure 12C






Figure 13





m_DataFormatProcessorMap
(in Figure 18A)

Figure 15

```

void CMonitorManager::stopMonitoring()
{
    TRACE("CMonitorManager::stopMonitoring \n");

    // 1. calls the function stopMonitoring() of
    // CUsageLogger.
    m_UsageLogger.stopMonitoring();

    // 2. calls the function getEventData() of
    // CUsageLogger. This function returns the usage
    // information, CAbsEventData, to CMonitorManager.
    CAbsEventData * loc_pAbsEventData = m_UsageLogger.getEventData();

    // 3. calls the function getFormatAndProtocolVector()
    // of CFormatProtocol_InformationBase. This function
    // returns the following to CMonitorManager: an int for
    // the data format, a list<int> for the communication
    // protocols, and a bool to indicate if the return
    // values (format and protocol) are valid.

    int loc_nFormat;
    list<int> loc_ProtocolVector;

    CProcessorBuilder loc_ProcessorBuilder;

    while(m_FormatProtocol_InformationBase.getFormatAndProtocolVector(
        loc_nFormat, loc_ProtocolVector)){

    // 4. calls the function createDataFormatProcessor()
    // of CProcessorBuilder. CMonitorManager passes an
    // int for the data format into this function. This
    // function returns the data format processor,
    // CAbsDataFormatter, to CMonitorManager.

        CAbsDataFormatter * loc_pAbsDataFormatter =
            loc_ProcessorBuilder.createDataFormatProcessor(loc_nFormat);

    // 5. calls the function formatEventData() of
    // CAbsDataFormatter. CMonitorManager passes the
    // usage information, CAbsEventData, into this
    // function. This function returns the formatted
    // usage information, CAbsFormattedEventData, to
    // CMonitorManager.

        CAbsFormattedEventData * loc_pAbsFormattedEventData =
            loc_pAbsDataFormatter->formatEventData(loc_pAbsEventData);

    // 6. calls the function createProtocolProcessor() of
    // CProcessorBuilder. CMonitorManager passes an int
    // for the communication protocol into this function.
    // The int is the first int from the protocol vector,
    // list<int>. This function returns the protocol
    // processor, CAbsProtocolProcessor, to CMonitorManager.

        for(list<int>::iterator loc_ProtocolVectorIterator =
            loc_ProtocolVector.begin(); loc_ProtocolVectorIterator NE
            loc_ProtocolVector.end(); loc_ProtocolVectorIterator ++){

```

Figure16A

```

        CAbsProtocolProcessor * loc_pAbsProtocolProcessor =
            loc_ProcessorBuilder.createProtocolProcessor(
                * loc_ProtocolVectorIterator);

// 7. calls the function processFormattedData() of
// CAbsProtocolProcessor. CMonitorManager passes the
// formatted usage information, CAbsFormattedEventData,
// into this function. This function returns a bool to
// CMonitorManager to indicate if the usage information
// was communicated using the protocol.

        loc_pAbsProtocolProcessor->processFormattedData(
            loc_pAbsFormattedEventData);

    }

// 8. steps 6 and 7 are repeated for each protocol,
// int, in the protocol vector, list<int>.
}

// 9. steps 3 through 8 are repeated for each format
// until the function getFormatAndProtocolVector()
// returns NO to CMonitorManager.
}

```

Figure 16B




Figure 17

Author: Avery Fong
3.3 CProcessorBuilder Class Specification

3.3.1 Function List

```
public:
    CProcessorBuilder();
    ~CProcessorBuilder();
    CAbsDataFormatter* createDataFormatProcessor(int in_nFormat);
    CAbsProtocolProcessor* createProtocolProcessor(int in_nProtocol),
```

```
private:
    void initDataFormatProcessorMap();
    void initProtocolProcessorMap();
```

Include the following functions to create the different data format processors and protocol processors.

```
CAbsDataFormatter* createCommaDataFormatter();
CAbsDataFormatter* createXMLDataFormatter();
CAbsProtocolProcessor* createSmtipProtocolProcessor();
CAbsProtocolProcessor* createFtpProtocolProcessor();
```

If new data formats or new protocols are added, then new functions to create them must be added.

Include the following typedef declarations for the functions that create the data format processors and protocol processors.

```
typedef CAbsDataFormatter* (*DataFormatProcessorBuilder) ();
typedef CAbsProtocolProcessor* (*ProtocolProcessorBuilder) ();
```

3.3.2 Class Attributes

Type	Attribute Name	Description
CAbsDataFormatter*	m_pDataFormatter	This attribute member points to the data format processor object. It is initialize to 0 in the constructor and the data format processor object is created by the function createDataFormatProcessor(). This function may be called multiple times so that it must delete the previous data format processor object pointed to by this attribute member before creating a new one. The destructor will delete the last data format processor object pointed to by this attribute member.
map<int, DataFormatProcessorBuilder>	m_ProtocolProcessorMap	This attribute member is a map of pointers to functions that create the data format processor. The key to this map is an int for the data format type. The value is a pointer to a function that creates the data format processor corresponding to the key. The pointers to the functions in the map are initialized in the function initDataFormatProcessorMap().
map<int, pair<CAbsProtocolProcessor*, ProtocolProcessorBuilder> >	m_ProtocolProcessorMap	This attribute member is a map of pointers to protocol processor objects and pointers to functions that create them. The key to this map is an int for the protocol processor type. The value is a pair consisting of a pointer to the protocol processor object and a pointer to a function that creates the protocol processor object. All the pointers to the protocol processor object are initialized to 0 and its corresponding functions are initialized by the function initProtocolProcessorMap(). The protocol processor objects are created by the function createProtocolProcessor(). The destructor will delete all the protocol processor objects pointed to by the map.

Figure 18A

```

3.3.3 Function Definitions
/////////////////////////////////////////////////////////////////
// Function:      CProcessorBuilder
// Description:    Constructor
// Preconditions:   None.
// Postconditions: None.
// Algorithm:      1. calls the private function
//                  initDataFormatProcessorMap().
//                  2. calls the private function
//                  initProtocolProcessorMap().
/////////////////////////////////////////////////////////////////

/////////////////////////////////////////////////////////////////
// Function:      ~CProcessorBuilder
// Description:    Destructor
// Preconditions:   None.
// Postconditions: None.
// Algorithm:      1. delete the object pointed to by m_pDataFormatter.
//                  2. iterate through the map, m_ProtocolProcessorMap.
//                  For each entry in the map, get the protocol
//                  processor object pointed to by the pair and delete
//                  the object.
/////////////////////////////////////////////////////////////////

/////////////////////////////////////////////////////////////////
// Function:      createDataFormatProcessor
// Description:    This function creates a data format processor
//                  object. The data format processor object created
//                  corresponds to the data format type in_nFormat.
// Preconditions:  The data format type must be valid.
// Postconditions: The pointer to the data format processor object,
//                  m_pDataFormatter, cannot be 0.
// Algorithm:      1. if m_pDataFormatter currently points to a data
//                  format processor object, then delete the object.
//                  2. creates a new data format processor object by
//                  calling the function in the map,
//                  m_DataFormatProcessorMap, that corresponds to the
//                  data format type, in_nFormat, and assign it to
//                  m_pDataFormatter.
//                  3. returns m_pDataFormatter.
/////////////////////////////////////////////////////////////////

/////////////////////////////////////////////////////////////////
// Function:      createProtocolProcessor
// Description:    This function creates a protocol processor object.
//                  The protocol processor object created corresponds
//                  to the protocol type in_nProtocol.
// Preconditions:  The protocol type must be valid.
// Postconditions: The pointer to the created protocol processor object
//                  cannot be 0.
// Algorithm:      1. for the protocol type, in_nProtocol, get the
//                  pair from the map that contains the pointer to
//                  protocol processor object and its corresponding
//                  pointer to the function that creates it.
//                  2. if the pointer to the protocol processor object
//                  is 0, then use its corresponding function to create
//                  it and assign it to the pointer in the map. Return
//                  the pointer to the protocol processor object.
//                  3. if the pointer points to a protocol processor
//                  object, then return this pointer.
/////////////////////////////////////////////////////////////////

```

Figure18B

```

/////////////////////////////////////////////////////////////////
// Private
// Function:      initDataFormatProcessorMap
// Description:   This function initializes all the function pointers
//               in the map m_DataFormatProcessorMap. If new data
//               formats are added, then this function must be
//               modified.
// Preconditions: None.
// Postconditions: None.
// Algorithm:     1. add entries to the map, m_DataFormatProcessorMap,
//               for each data format type. The key will be the
//               data format type and the value will be the pointer
//               to the corresponding function that creates the
//               data format processor.
//               2. for data format type 1, the function pointer
//               points to createCommaDataFormatter().
//               3. for data format type 2, the function pointer
//               points to createXMLDataFormatter().
/////////////////////////////////////////////////////////////////

/////////////////////////////////////////////////////////////////
// Private
// Function:      initProtocolProcessorMap
// Description:   This function initializes all the pairs of pointers
//               in the map m_ProtocolProcessorMap. If new protocols
//               are added, then this function must be modified.
// Preconditions: None.
// Postconditions: None.
// Algorithm:     1. add entries to the map, m_ProtocolProcessorMap,
//               for each protocol type. The key will be the
//               protocol type and the value will be a pointer to
//               the protocol processor object and a pointer to
//               the corresponding function that creates the
//               protocol processor. All pointers to the protocol
//               processor objects will be set to 0.
//               2. for protocol type 1, the function pointer
//               points to createSmtpprotocolProcessor().
//               3. for protocol type 2, the function pointer
//               points to createFtpProtocolProcessor().
/////////////////////////////////////////////////////////////////

/////////////////////////////////////////////////////////////////
// Function:      createCommaDataFormatter
// Description:   This function creates and returns a comma data
//               formatter object.
// Preconditions: None.
// Postconditions: The pointer to the created comma data formatter
//               object cannot be 0.
// Algorithm:     1. creates and returns an object of the class
//               CCommaDataFormatter.
/////////////////////////////////////////////////////////////////

/////////////////////////////////////////////////////////////////
// Function:      createXMLDataFormatter
// Description:   This function creates and returns an XML data
//               formatter object.
// Preconditions: None.
// Postconditions: The pointer to the created XML data formatter
//               object cannot be 0.
// Algorithm:     1. creates and returns an object of the class
//               CXMLDataFormatter.
/////////////////////////////////////////////////////////////////

```

Figure 18C

```

////////////////////////////////////
// Function:      createSmtProtocolProcessor
// Description:    This function creates and returns an SMTP protocol
//                processor object.
//
// Preconditions:  None.
// Postconditions: The pointer to the created smtp protocol processor
//                object cannot be 0.
//
// Algorithm:      1. creates and returns an object of the class
//                CSmtProtocolProcessor.
////////////////////////////////////

```

```

////////////////////////////////////
// Function:      createFtpProtocolProcessor
// Description:    This function creates and returns an FTP protocol
//                processor object.
//
// Preconditions:  None.
// Postconditions: The pointer to the created ftp protocol processor
//                object cannot be 0.
//
// Algorithm:      1. creates and returns an object of the class
//                CFtpProtocolProcessor.
////////////////////////////////////

```

Figure 18D





Figure 19



Format And Protocol Information Base Package Class Structure

Figure 20




Figure 21




Figure 22

Author: Tetsuro Motoyama

5.2 CFormatProtocol_InformationBase Class Specification**5.2.1 Function List**

```

public:
    CFormatProtocol_InformationBase();
    ~CFormatProtocol_InformationBase();
    void storeFormatAndProtocol(int in_nFormat, int in_nProtocol);
    bool getFormatAndProtocolVector(int & out_nFormat, list<int> & out_ProtocolVector);

```

```

private:
    void setDefaultFormatAndProtocol();

```

5.2.2 Class Attributes

Type	Attribute Name	Description
map<int, list<int> >	m_FormatProtocolVectorMap	The key is a format value, and the list is the list of protocol values associated to the key. Because subscripting [] is not needed in this implementation, list is used for the vector implementation. This map is used to return the necessary information for getFormatAndProtocolVector function Note: > > is > space > to distinguish from ">>" that is used by ostream.
map<int, list<int> >	m_ProtocolFormatVectorMap	The key is a protocol value, and the list is the list of format values associated to the key. Because subscripting [] is not needed in this implementation, list is used for the vector implementation. This map is used to modify the map above if the protocol can take only one format.
bool	m_bFirstGetCall	This flag is used to call the function in CProtocolRestrictionCheck. The constructor set this to be true. The function, getFormatAndProtocolVector, sets it to be false
map<int, list<int> >::iterator	m_FormatProtocolVectorMapIterator	Iterator used to iterate the map.
CFormatProtocolCombinationCheck	m_FormatProtocolCombinationCheck	This object is to check the combination of format and protocol
CProtocolRestrictionCheck	m_ProtocolRestrictionCheck	This object is to check the protocol restriction. Currently, the only restriction is if protocol can have only one format support.

5.2.3 Function Definitions

```

////////////////////////////////////
//Function:      CFormatProtocol_InformationBase
//Description:   Constructor
//Preconditions:  None
//Postconditions: None
//Algorithm:     Set m_bFirstGetCall to true
////////////////////////////////////

```

```

////////////////////////////////////
//Function:      ~CFormatProtocol_InformationBase
//Description:   Destructor
//Preconditions:  None
//Postconditions: None
//Algorithm:     Default
////////////////////////////////////

```

Figure 17A
23A

```

////////////////////////////////////
//Function:      storeFormatAndProtocol
//Description:   Check the passed format and protocol values
//              to be valid or not. If valid, store the
//              values into the two maps
//Preconditions:  None
//Postconditions: None
//Algorithm:     1. Send two values to check the combination
//              through isFormatProtocolCombinationOK
//              function.
//              2. Check the return bool value.
//              3. If yes, save format and protocol values
//              into two maps (Figure 5.4 of the
//              Specification, Q6-DJ04-08)
//              Else, do nothing.
////////////////////////////////////

```

```

////////////////////////////////////
//Function:      getFormatAndProtocolVector
//Description:   The function returns a format and a list
//              of protocol values associated with the
//              format through two parameters. The function
//              returns true if a format and list are
//              returned, false otherwise.
//Preconditions:  None
//Postconditions: The format value is within the range.
//              The list is not empty and contains the values
//              within the range.
//Algorithm:     1. If m_bFirstGetCall (Figure 5.5 of the
//              Specification Q6-DJ04-08)
//              1.1 call the function to check the protocol
//              restriction.
//              1.2 check if m_FormatProtocolVectorMap is
//              empty. If empty, set it to default
//              values of format and protocol by calling
//              setDefaultFormatAndProtocol function.
//              1.3 set the iterator to begin().
//              1.4 set m_bFirstGetCall to be false
//              2. If iterator is end, return false.
//              else (Figure 5.6 of the Specification
//              Q6-DJ04-08)
//              get format and list to return and set
//              return parameters.
//              increment iterator.
//              Return true.
////////////////////////////////////

```

```

////////////////////////////////////
//Private Function: setDefaultFormatAndProtocol
//Description:   The function sets the default values for
//              format and protocol in the map.
//Preconditions: The m_FormatProtocolVectorMap is empty.
//Postconditions: The map contains one default format and a
//              protocol list with one default protocol.
//Algorithm:     Set the map with the default values.
////////////////////////////////////

```

Figure 17B
23B

Author: Tetsuro Motoyama

5.3 CFormatProtocolCombinationCheck Class Specification

5.3.1 Function List

```
public:
    CFormatProtocolCombinationCheck();
    ~CFormatProtocolCombinationCheck();
    bool isFormatProtocolCombinationOK(const int in_nFormat, const int in_nProtocol);

private:
    void initMatrix();
```

5.3.2 Class Attributes

Type	Attribute Name	Description
map<int, set<int> >	m_CombinationMatrix	Key is the format. The set contains the protocols that are valid for the particular format

5.3.3 Function Definitions

```
////////////////////////////////////
//Function:      CFormatProtocolCombinationCheck
//Description:    Constructor
//Preconditions:  None
//Postconditions: None
//Algorithm:      call initMatrix
////////////////////////////////////
```

```
////////////////////////////////////
//Function:      ~CFormatProtocolCombinationCheck
//Description:    Destructor
//Preconditions:  None
//Postconditions: None
//Algorithm:      Default
////////////////////////////////////
```

```
////////////////////////////////////
//Function:      isFormatProtocolCombinationOK
//Description:    Check the passed format and protocol values
//                to be valid or not. If valid, return yes,
//                no otherwise
//Preconditions:  None
//Postconditions: None
//Algorithm:      1. Use find function of the Matrix for
//                in_nFormat
//                2. If returned iterator is end, return No
//                3. get the set value for the key format
//                4. Use the find function of the set for
//                in_nProtocol
//                5. if returned iterator is end, return no
//                6. return yes
////////////////////////////////////
```

Figure 18A
24A

```
////////////////////////////////////  
//Private Function:  initMatrix  
//Description:       This function initializes m_CombinationMatrix.  
//                  If new formats or protocols are added, this  
//                  function must be modified.  
//Precondition:      None  
//Postcondition:     None  
//Algorithm:         1. Create the local set<int>  
//                  2. for each format  
//                      2.1 fill in the local set  
//                        with the protocol numbers  
//                        that are valid for the format,  
//                        using insert function  
//                  2.2 m_CombinationMatrix[format]  
//                      = local set  
//                  2.3 clear local set  
////////////////////////////////////
```

Figure 18B
24B

Author: Tetsuro Motoyama

5.4 CProtocolRestrictionCheck Class Specification**5.4.1 Function List**

```

public:
    CProtocolRestrictionCheck();
    ~CProtocolRestrictionCheck()
    void getFormatProtocolVectorMapAfterCheckingProtocolRestriction
        (map<int, list<int>> & inOut_Map, const map<int, list<int>> & in_Map);

private:
    void initOneFormatRestriction();
    void oneFormatRestriction
        (map<int, list<int>> & inOut_Map, const map<int, list<int>> & in_Map);

```

5.4.2 Class Attributes

Type	Attribute Name	Description
vector<bool>	m_bOneFormatRestriction	Array size should be protocol size+1. The position corresponds to the protocol.

5.4.3 Function Definitions

```

////////////////////////////////////
//Function:      CProtocolRestrictionCheck
//Description:   Constructor
//Preconditions:  None
//Postconditions: None
//Algorithm:     call initOneFormatRestriction
////////////////////////////////////

```

```

////////////////////////////////////
//Function:      ~CProtocolRestrictionCheck
//Description:   Destructor
//Preconditions:  None
//Postconditions: None
//Algorithm:     Default
////////////////////////////////////

```

```

////////////////////////////////////
//Function:      getFormatProtocolVectorMapAfterCheckingProtocolRestriction
//Description:   Check the restriction on the protocol.
//              Currently, there is only one possible restriction
//              defined in the requirements. If there are more
//              restrictions, more private functions should be
//              added and called.
//Preconditions:  None
//Postconditions: None
//Algorithm:     1. Call oneFormatRestriction function
////////////////////////////////////

```

Figure 19A
25A

```

//Private Function: initOneFormatRestriction
//Description: This function initialize the attribute
//              m_bOneFormatRestriction. If more protocols are
//              added, this initialization must be modified.
//Preconditions: None
//Postconditions: None
//Algorithm: 1. use assign(size+1,false) to initialize the
//              vector to false.
//            2. set the entries of true.
//            Note: for class debug version, use
//                  ifdef and
//                  bool & pos1 = m_bOneFormatRestriction[1];
//                  bool & pos2 = m_bOneFormatRestriction[2];
//                  and so on to be able to see and to
//                  change the value.
////////////////////////////////////

////////////////////////////////////
//Private Function: oneFormatRestriction
//Description: This function receives two maps and if the one
//              restriction is true for given protocol, the
//              content of inOut_Map (m_FormatProtocolVectorMap)
//              is adjusted accordingly.
//Preconditions: None
//Postconditions: None
//Algorithm: Iterate over the in_Map (m_ProtocolFormatVectorMap)
//            1. get the key (pkey)
//            2. If m_bOneFormatRestriction[pkey]
//                2.1 get the value list of in_Map for the key
//                2.2 local int lastFormat = back(),
//                2.3 iterate over the list
//                    if *iterator NE lastFormat
//                        iterate over inOut_Map[*iterator] list
//                            if the value EQ pkey
//                                erase the entry from the list
//            3. Iterate over inOut_Map
//                if value list is empty,
//                    erase the entry from inOut_Map
//-----
//Example:      0 1 2 3 4
// m_bOneFormatRestriction = [0,0,1,0,1] (four protocols)
//                  0: false, 1: true
// inOut_Map (m_FormatProtocolVectorMap)
// = [ 1, <1,2,3,4>      --> <1, 2, 3>
//    2, <2,1,3,4>      --> <1, 3>
//    3, <3,4,1,2>      --> <3, 4, 1>
//    4, <2,4>          --> <>
// in_Map (m_ProtocolFormatVectorMap)
// = {1, <1, 3, 2>
//    2, <4, 3, 2, 1>
//    3, <1, 3, 2>
//    4, <4, 2, 1, 3>}
//
// pkey = 1 m_bOneFormatRestriction[1] = 0
// pkey = 2 m_bOneFormatRestriction[2] = 1
// value list = <4, 3, 2, 1> (2.1)
// lastFormat = 1 (2.2)
// 4 != 1
// inOut_Map[4] = <2,4>
// erase value 2 <4>
// 3 != 1
// inOut_Map[3] = <3,4,1,2>
// erase value 2 <3,4,1>
// 2 != 1
// inOut_Map[2] = <2,1,3,4>
// erase value 2 <1,3,4>
// 1 == 1
// pkey = 3 m_bOneFormatRestriction[3] = 0

```

Figure 19B
25B

Declaration, Power of Attorney and Petition

Page 1 of 3

WE (I) the undersigned inventor(s), hereby declare(s) that:

My residence, post office address and citizenship are as stated below next to my name,

We (I) believe that we are (I am) the original, first and joint (sole) inventor(s) of the subject matter which is claimed and for which a patent is sought on the invention entitled

Method and System of Remote Diagnostic, Control and Information Collection Using a Dynamic

Linked Library of Multiple Formats and Multiple Protocols with Restriction on Protocol

the specification of which

☒ is attached hereto.

☐ was filed on _____ as

Application Serial No. _____

and amended on _____.

☐ was filed as PCT international application

Number _____

on _____,

and was amended under PCT Article 19

on _____ (if applicable).

We (I) hereby state that we (I) have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

We (I) acknowledge the duty to disclose information known to be material to the patentability of this application as defined in Section 1.56 of Title 37 Code of Federal Regulations.

We (I) hereby claim foreign priority benefits under 35 U.S.C. § 119(a)-(d) or § 365(b) of any foreign application(s) for patent or inventor's certificate, or § 365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed. Prior Foreign Application(s)

Application No.	Country	Day/Month/Year	Priority Claimed
_____	_____	_____	<input type="checkbox"/> Yes <input type="checkbox"/> No
_____	_____	_____	<input type="checkbox"/> Yes <input type="checkbox"/> No
_____	_____	_____	<input type="checkbox"/> Yes <input type="checkbox"/> No

We (I) hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below.

(Application Number)

(Filing Date)

(Application Number)

(Filing Date)

We (I) hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s), or under § 365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR § 1.56 which became available between the filing date of the prior application and the national or PCT International filing date of this application.

Application Serial No.

Filing Date

Status (pending, patented,
abandoned)

Application Serial No.	Filing Date	Status (pending, patented, abandoned)

And we (I) hereby appoint: Norman F. Oblon, Reg. No. 24,618; Marvin J. Spivak, Reg. No. 24,913; C. Irvin McClelland, Reg. No. 21,124; Gregory J. Maier, Reg. No. 25,599; Arthur I. Neustadt, Reg. No. 24,854; Richard D. Kelly, Reg. No. 27,757; James D. Hamilton, Reg. No. 28,421; Eckhard H. Kuesters, Reg. No. 28,870; Robert T. Pous, Reg. No. 29,099; Charles L. Gholz, Reg. No. 26,395; William E. Beaumont, Reg. No. 30,996; Jean-Paul Lavalleye, Reg. No. 31,451; Stephen G. Baxter, Reg. No. 32,884; Richard L. Treanor, Reg. No. 36,379; Steven P. Weihrouch, Reg. No. 32,829; John T. Goolkasian, Reg. No. 26,142; Richard L. Chinn, Reg. No. 34,305; Steven E. Lipman, Reg. No. 30,011; Carl E. Schlier, Reg. No. 34,426; James J. Kulbaski, Reg. No. 34,648; Richard A. Neifeld, Reg. No. 35,299; J. Derek Mason, Reg. No. 35,270; Surinder Sachar, Reg. No. 34,423; Jeffrey B. McIntyre, Reg. No. 36,867; William T. Enos, Reg. No. 33,128; Michael E. McCabe, Jr., Reg. No. 37,182; Bradley D. Lytle, Reg. No. 40,073; and Michael R. Casey, Reg. No. 40,294; our (my) attorneys, with full powers of substitution and revocation, to prosecute this application and to transact all business in the Patent Office connected therewith; and we (I) hereby request that all correspondence regarding this application be sent to the firm of OBLON, SPIVAK, MCCLELLAND, MAIER & NEUSTADT, P.C., whose Post Office Address is: Fourth Floor, 1755 Jefferson Davis Highway, Arlington, Virginia 22202.

We (I) declare that all statements made herein of our (my) own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

Tetsuro MOTOYAMA

NAME OF FIRST SOLE INVENTOR

Tetsuro Motoyama
Signature of Inventor

Date

16 May 2000

Residence: 829 Standhal Lane

Cupertino, CA 95014

Citizen of: USA

Post Office Address: Same As Above

004750" 3165460

Avery FONG

NAME OF SECOND JOINT INVENTOR

Avery Fong
Signature of Inventor

16 May 2000
Date

NAME OF THIRD JOINT INVENTOR

Signature of Inventor

Date

NAME OF FOURTH JOINT INVENTOR

Signature of Inventor

Date

NAME OF FIFTH JOINT INVENTOR

Signature of Inventor

Date

Residence: 25797 Annie Court

Castro Valley, CA 94552

Citizen of: USA

Post Office Address: Same As Above

Residence: _____

Citizen of: _____

Post Office Address: _____

Residence: _____

Citizen of: _____

Post Office Address: _____

Residence: _____

Citizen of: _____

Post Office Address: _____